

EPDM PRIMER and BONDING AGENT

EPDM Primer and **Bonding Agent** are a specially formulated vulcanizing compounds engineered to provide maximum adhesion and lifespan when splicing peroxide-cured EPDM belts with heat resistance ratings from 204 °C - 371 °C (400 °F - 700 °F)

FEATURES:

- Prepares a clean work surface for tackifying and increases the bond for splicing.
- Tested for compatibility with all major conveyor belting manufacturer specifications.
- Brushable consistency for ease of application.
- Superior bonding to peroxide-cured EPDM belts.
- Flammable



Primer Properties:

Rubber Colour: Black
Base Polymer: EPDM Rubber
Solids (wt.): 20-25%
Calculated Coverage: 13.4 M² (144 ft.²)
Flash Point: 15 °C (59 °F)
Shelf Life: 6 Months at 21 °C (70 °F) or
12 Months at 10 °C (50 °)

EPDM PRIMER

PRODUCT CODE	WEIGHT (METRIC/IMPERIAL)
AA-HFEPDM-001	750 gr / 1.7 Lbs.

Bonding Agent Properties:

Rubber Colour: Black
Base Polymer: EPDM Rubber
Solids (wt.): 15-20%
Calculated Coverage: 13.4 M² (144 ft.²)
Flash Point: 7 °C (45 °F)
Shelf Life: 6 Months at 21 °C (70 °F) or
12 Months at 10 °C (50 °)

EPDM BONDING AGENT

PRODUCT CODE	WEIGHT (METRIC/IMPERIAL)
AA-HCEPDM-001	1 kg / 2.2 Lbs.

NA

Shaw Almix
Europe B.V.
☎ 31 646648648

Shaw Almix
Industries, Canada
☎ 1 905 643 7750

Shaw Almix
Industries, Canada
☎ 1 705 746 5884

Shaw Almix
Fusion, LLC, U.S.A.
☎ 1 404 292 8600

Shaw Almix
Africa (Pty) Ltd.
☎ 27 11 794 8262

 **ALMEX**
GROUP
www.almex.com 1.800.977.5423