

# AMS-2102

## LONG-TERM DUST CONTROL

Applied at Last transfer before material discharge point. **AMS-2102** mixes easily with water spray system through doing injection that is applied Inline by nozzles and manifolds at the last transfer point to stockpile or loading discharge point for truck, rail, barge or ship transport. The formula provides dual benefit of immediate dust control and long-term fine micron particle binding, embedding the particles into the main material flow for up to 60 days, providing long term dust control from loading, through transit and to final unloading point.

- Applied at last transfer point before stockpile.
- 30-60 day Long-term coal cooling.

### FEATURES:

- AMS 2102 polymer surfactant blend
- The solution is applied at the LAST transfer point before material discharge
- Long-term dust control binder for 10 micron inhalable dust down to 2.5 micron respirable dust

Votech Dust Suppression Solutions work well, are competitively priced and save water use and labor time onsite.

Contact Us to discuss what Votech solutions would work for you and to request a product demonstration.

GL

Shaw Almex  
Mining Equip. (Tianjin) Co. Ltd.  
☎ +86 (22) 2388-9075

PT. Shaw Almex  
Indonesia  
☎ +61 488 780243

Shaw Almex  
Pacific Pty Ltd. Qld  
☎ 61 7 4774 2011

Shaw Almex  
Pacific Pty Ltd. WA  
☎ 61 8 9358 5860

Shaw Almex  
India PVT. Ltd.  
☎ 91-129-2274624

 **ALMEX**  
GROUP  
www.almex.com 1-800-977-5423