

PUMPPACK 1000

Suitable for Inline Dust Control
 Applications up to 1000 TPH. Chemical
 Injection into water spray controls dust
 with less moisture while recapturing
 material particles embedding them back
 into the main material flow.

FEATURES:

- Compact arrangement with Multistage Pump and Dosing Pump
- Programmable PLC interface
- Suitable for Inline Dust Control Applications up to 1000 TPH belt conveyor capacity
- NEMA Rated IP 55 Enclosure
- Outdoor Weatherproof Design
- Easy to operate External Controls
- For Single Line Point Applications
- Specially designed for surfactant-based chemical applications
- Votech Dust Suppression Solutions work well, are competitively priced and save water use and labour time onsite



SPECIFICATIONS

Capacity:	Max 15 M ³ (529.7 ft ³) with Tt Head of 40 M (131 ft)
Working Pressure:	Max 10 bar (145 PSI)
Power Requirements:	1 x 7.5 Kw/3ph/380 V
Dimensions:	1200 mm (H) X 500 mm (W) X 600 mm (L) (47.2" x 19.7" x 23.6")
Operating Mode:	Manual and Fully automatic
Display Control:	Wientek HMI 178 mm (7") Interactive Touch Screen
Inlet Port:	Fresh water, threaded, 50.8 mm (2") diameter
Chemical Din connector:	9.5 mm (3/8") diameter
Outlet Port:	Solution mixture threaded type 50.8 mm (2") diameter

GL

Shaw Almix
 Mining Equip. (Tianjin) Co. Ltd.
 ☎ +86 (22) 2388-9075

PT. Shaw Almix
 Indonesia
 ☎ +61 488 780243

Shaw Almix
 Pacific Pty Ltd. Qld
 ☎ 61 7 4774 2011

Shaw Almix
 Pacific Pty Ltd. WA
 ☎ 61 8 9358 5860

Shaw Almix
 India PVT. Ltd.
 ☎ 91-129-2274624

ALMEX
 GROUP
 www.almex.com 1-800-977-5423