

PUMPPACK 2200

Suitable for Inline Applications and Hopper/Dump Pocket Dust Control Applications up to 1200 TPH conveyor capacity.

FEATURES:

- Compact arrangement with 2 Multistage Pumps set-up in redundancy with Mixing Unit
- Programmable PLC Interface
- Suitable for Large Hopper, Dump Pocket and Crusher Applications
- Suitable for Inline Dust Control Applications up to 1200 TPH belt conveyor capacity
- 2200 Indoor or 2200-WP Outdoor; Weatherproof Design
- Easy to operate External Controls
- For Dual Application Point Locations
- Specially designed for surfactant based chemical applications

OPTIONS:

2200-WP: Components per about with NEMA-Rated IP 55 Enclosure.



SPECIFICATIONS

Capacity:	Max 20 M ³ (706.3 ft ³) with Tt Head of 60 M (196.9 ft)
Working Pressure:	Max 10 bar (145 PSI)
Power Requirements:	2 x 11 Kw/3ph/380 V
Dimensions:	1830 mm (H) X 1080 mm (W) X 1080 mm (L) (72" x 42.5" x 42.5")
Operating Mode:	Manual and Fully automatic
Display Control:	Wientek HMI 178 mm (7") Interactive Touch Screen
Inlet Port:	Fresh water, threaded, 76.2 mm (3") diameter. chemical threaded 50.8 mm (2") diameter
Outlet Port:	Solution mixture threaded type 76.2 mm (3") diameter

GL

Shaw Almix
Mining Equip. (Tianjin) Co. Ltd.
☎ +86 (22) 2388-9075

PT. Shaw Almix
Indonesia
☎ +61 488 780243

Shaw Almix
Pacific Pty Ltd. Qld
☎ 61 7 4774 2011

Shaw Almix
Pacific Pty Ltd. WA
☎ 61 8 9358 5860

Shaw Almix
India PVT. Ltd.
☎ 91-129-2274624

ALMEX
GROUP
www.almex.com 1-800-977-5423