

ALMEX PUMPPACK 5500

With chemical flow on-demand, The PumpPack 5500 is excellent for Intermittent Activation Spray Systems.

The 5500 has a weather-proof design suitable for multiple inline dust control Application point locations and large multi-application point locations, up to a combined 4000 TPH conveyor capacity.

FEATURES:

- Compact arrangement: 2 x Multi-stage-Pump set-up in redundancy with mixing unit
- Programmable PLC interface
- Suitable for Large Hopper, Dump Pocket and Crusher Applications
- For inline Dust Control Applications with up to 4000 TPH belt conveyor capacity
- Easy-to-Operate External Controls
- NEMA Rated IP 55 Er
- Weatherproof Design
- For Single and Dual Application Point locations and Large Containment Applications -specially designed for use with surfactant based chemical treatments



SPECIFICATIONS

Capacity:	Max 25 M ³ (882.9 ft ³) with Tt Head of 60 M (196.9 ft)
Working Pressure:	Max 10 bar (145 PSI)
Power Requirements:	1 x 15 Kw/3ph/380 V
Dimensions:	1200 mm (H) X 1430 mm (W) X 500 mm (L) (47.2" x 56.3" x 19.7")
Display Control:	Wientek HMI 178 mm (7") Interactive Touch Screen
Inlet Port:	Fresh water, threaded, 76.2 mm (3") diameter
Solution Outlet:	Chemical threaded 12.7 mm (1/2") diameter
Chemical Inlet:	Solution mixture threaded type 76.2 mm (3") diameter

GL

Shaw Almex
Mining Equip. (Tianjin) Co. Ltd.
☎ +86 (22) 2388-9075

PT. Shaw Almex
Indonesia
☎ +61 488 780243

Shaw Almex
Pacific Pty Ltd. Qld
☎ 61 7 4774 2011

Shaw Almex
Pacific Pty Ltd. WA
☎ 61 8 9358 5860

Shaw Almex
India PVT. Ltd.
☎ 91-129-2274624

ALMEX
GROUP
www.almex.com 1-800-977-5423